

2017 Evo 200

Engine

Type: Single cylinder, 2-stroke, liquid-cooled w/ reed valve

Bore: 64mm
Stroke: 60.5mm
Displacement: 194.6 cc
Compression Ratio: 11.8:1

Ignition: Electronic 12 volt, 85 watt w/ dual-map switch (aggressive or soft settings)

Spark Plug NGK BR7ES

Lubrication: Pre-mix (synthetic oil)
Carburetor: Keihin PWK 28mm

Clutch: Wet multi-disc w/ cush-drive basket

Transmission: 6-speed

Chassis

Frame: Aluminum beam, single wave **Hydro-Formed** w/built in fuel tank

Wheelbase: 51.4"
Seat Height: 26"
Ground Clearance: 12.2"
Footrest Height: 13.6"

Dry Weight: **145 lbs**. dry
Fuel Tank Capacity: .75 US gallons
Front Suspension: 38mm Paioli

Rear Suspension: Adjustable single shock, aluminum bodied, with nitrogen valve including linkage

Front Wheel Travel: 6.5" Rear Wheel Travel: 7.1"

Final Gearing: 11t front, 42t rear

Front Brake: 185mm rotor w/ 4-piston caliper
Rear Brake: 160mm rotor w/ twin-piston caliper

Front/Rear Rim: 21" (Front) 18" (Rear)

Front/Rear Tire: Michelin Trial

Warranty: 6 month Limited Warranty

MSRP: **\$7199.00**

Additional information on all models including manuals, accessories and parts books are available online at BetaUSA.com under Support.



^{*}specifications subject to change without notice.