



2012 Evo 250

## Engine

Type:	Single cylinder, 2-stroke, liquid-cooled w/ reed valve
Bore:	72.5mm
Stroke:	60.5mm
Displacement:	249.7cc
Compression Ratio:	8.9:1
Ignition:	Electronic 12 volt, 85 watt w/ dual-map switch (aggressive or soft settings)
Spark Plug	NGK BR7ES
Lubrication:	Pre-mix (synthetic oil)
Carburetor:	Keihin PWK 28mm
Clutch:	Wet multi-disc w/ cush-drive basket
Transmission:	6-speed

## Chassis

Frame:	Aluminum beam, single wave w/ built in fuel tank
Wheelbase:	51.4"
Seat Height:	26"
Ground Clearance:	12.2"
Footrest Height:	13.6"
Dry Weight:	149.9 lbs. dry
Fuel Tank Capacity:	0.7 US gallons
Front Suspension:	38mm Paioli including hard-coated tubes
Rear Suspension:	Single shock, aluminum bodied including linkage, adjustable dampening
Front Wheel Travel:	6.5"
Rear Wheel Travel:	7.1"
Final Gearing:	11t front, 41t rear
Front Brake:	185mm rotor w/ 4-piston caliper
Rear Brake:	160mm rotor w/ twin-piston caliper
Front/Rear Rim:	21" (Front) 18" (Rear)
Front/Rear Tire:	Michelin Trial
Warranty:	6 month Limited Warranty

**MSRP: \$7499.00**

\*specifications subject to change without notice.

Additional information on all models including manuals, accessories and parts books are available online at [AmericanBeta.com](http://AmericanBeta.com) under Support.

